

## RESIFA™ SOLESPHERE™ H-Series

### Product Description

RESIFA™ SOLESPHERE™ H series is a synthetic spherical silica having low cohesiveness and high fluidity. We have two types of H series: normal type and high oil absorption type. The second type has over twice the absorption capacity of the first.

SOLESPHERE™ high oil absorption type has unique characteristics. It is very bulky and disperses easily. SOLESPHERE™ H series is available in a variety of particle sizes.

### Normal Type

		H-31	H-51	H-121	H-201
Mean particle size	µm	3	5	12	20
Specific surface area	m <sup>2</sup> /g	800	800	800	800
Pore volume	mL/g	1	1	1	1
Pore diameter	nm	5	5	5	5
Oil absorption	mL/100g	150	150	150	150
Bulk density	g/mL	0.18	0.23	0.33	0.36
Specific gravity	g/mL	2.16	2.16	2.16	2.16

### High Oil Absorption Type

		H-52	H-122	H-33	H-53
Mean particle size	µm	5	12	3	5
Specific surface area	m <sup>2</sup> /g	700	700	700	700
Pore volume	mL/g	2	2	2	2
Pore diameter	nm	10	10	11	11
Oil absorption	mL/100g	300	300	400	400
Bulk density	g/mL	0.11	0.16	0.08	0.09
Specific gravity	g/mL	2.14	2.14	2.12	2.12

INCI: Silica

Usage levels: 1-5%

Certifications: ECOcert/Cosmos

## RESIFA™ SOLESPHERE™ H-Series

### SOLESPHERE™ Particle Structure

- Spherical and non cohesive
- High oil absorption capacity unlike any other
- Applied as new functional material filler

### Application Information

#### Cosmetics and Personal Care

SOLESPHERE™ silica gels are used as additives in cosmetic and personal care applications such as make-up, skin care products, deodorants and fragrances.

#### Resins and Polymer Compounds

When added to polymer formulations, SOLESPHERE™ silica gels offer anti blocking and improved dielectric insulation properties. SOLESPHERE™ also provides good UV and hardness properties as an additive for 3D resins.

#### Catalyst Supports

SOLESPHERE™ is used as a catalyst support carrier particularly with polyolefin manufacturing processes.

#### Paper Coating

By adding SOLESPHERE™ to paper coating formulations, surface hardness can be increased and matting effect improved.

#### Coatings

SOLESPHERE™ silica gels are used to improve the matting effect in coatings, as a thickener for paints, and for specialized paints for electronic materials.

RESIFA™ and SOLESPHERE™ are registered trademarks of AGC Inc.

### Additional Information

#### Packaging

SOLESPHERE™ is packaged in a triple lined polyethylene bag contain in a cardboard carton. The box unit is 20 kgs for SOLESPHERE™ H-31, H-51 and H-121. For SOLESPHERE™ H-51, N-122, H-33 and H-53, the box unit is 10 kgs. There are 18 boxes per pallet.

#### Storage and Shelf Life

SOLESPHERE™ silica gels have a shelf life of 2 years from the date of manufacture when stored in the original, unopened package between 10 and 40 C.

#### Safety and Handling

A Safety Data Sheet for this product may be obtained from your local AGC representative. Before handling, it is recommended to review the Safety Data Sheet for handling, safe, and health information.



## RESIFA™ SOLESPHERE™ H-Series

### Product Specifications

Additional product specifications and information can be obtained by request.

**AGC Chemicals Americas, Inc.**  
55 E. Uwchlan Avenue, Suite 201  
Exton, PA 19341, USA

Telephone: +1 610-423-4300  
Toll Free (US only): 800-424-7833  
Fax: +1 610-423-4305

**www.agcchem.com**  
Visit our website for compliance  
information and industry certifications.

The AGC logo consists of the letters "AGC" in a bold, blue, sans-serif font, with a small red square positioned above the letter "C".

**AGC Chemicals Company  
AGC Inc.**

Shin-Marunouchi Bldg.  
1-5-1 Marunouchi  
Chiyoda-ku, Tokyo  
100-8405 Japan  
Tel: +81-3-3218-5438  
www.agc-chemicals.com

**AGC Asia Pacific Pte., Ltd.**

460 Alexandra Road  
#32-01 mTower  
Singapore 119963  
Tel: +65 6273 5656  
www.agc-asiapacific.com

**AGC Chemicals Trading  
(Shanghai) Inc.**

Room 4008/09, F40, T1  
Raffles City Changning  
No.1133 Changning Road  
Shanghai, China 200051  
Tel: +86-21-6386-2211  
www.agc-chemicals.com/cn/zh/

**AGC Chemicals Europe, Ltd.**

Hillhouse International  
Fleetwood Road North  
Thornton-Cleveleys  
FY5 4QD  
United Kingdom  
Tel: +44 (0) 1253 209560  
www.agcce.com

**AGC Chemicals Europe, Ltd.  
Commercial Centre**

World Trade Center, Zuidplein 80  
1077 XV Amsterdam, Netherlands  
Tel: +31-(0)-20-880-41-70  
www.agcce.com

**AGC Vidros do Brasil Ltda.**

Estrada Municipal Doutor Jaime  
Eduardo Ribeiro Pereira, 500  
Jardim Vista Alegre  
Guaratinguetá, SP, Brasil  
CEP 12523-671  
Tel: +55 12 3127-7100  
www.agcchem.com/pt-br/



**Chemistry  
for a Blue Planet**  
AGC Chemicals

# AGC

**AGC Chemicals Americas, Inc.**

55 E. Uwchlan Avenue, Suite 201  
Exton, PA 19341  
United States of America

Telephone: +1 610-423-4300  
Toll Free (US only): 800-424-7833  
Fax: +1 610-423-4305

**www.agcchem.com**

Visit our website for compliance information and industry certifications.

The information provided herein is related only to the specific product designated and may not be applicable where such product is used in combination with any other materials or in any process.

NO REPRESENTATION OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE, ARE MADE HEREUNDER.

The user of this product has the sole responsibility to determine the suitability of the product for any use and manner of use intended. This document may be revised after its issuance, and the user is advised to use the latest revision.

This information should be used as a guide only and not to establish specification limits or design criteria.